DIELECTRIC MAXI OVERBOOTS



Power Generation Power Distribution Construction Telecommunications Transport

A Class 1 electrically insulating dielectric overboot with a vulcanized rubber sole for superior slip resistance. The Workmaster™ Maxi Dielectric overboot is designed to be worn over safety boots and allows live working at up to 7.5kV with every boot tested at 20kV for ASTM F1117.

Features

- Injection moulded using our proprietary Dielectric compound for a seamless boot with excellent electrical insulation properties
- Ingenious rear entry design ensures the boot is quick and easy to fit and remove
- Ideal for personnel who have to continually enter and exit hazardous areas
- Single piece injection moulded construction with integral moulded fastener ensures there are no seams or mounting/ fastener holes to leak
- Vulcanized rubber sole for greatly improved slip resistance in wet and oily conditions (SRC)
- Durable, cut-resistent vulcanised rubber sole, significantly extends working life, even in harsh terrain
- Heat resistant sole EN 20347:2011 HRO, 60 seconds at 300°C
- Fuel and oil resistant sole
- Kick-off lug
- CE marked with date and year of manufacture
- REACH Compliant

Care

- Machine washable at up to 40°C
- · Shelf life of over 10 years

High Voltage Test

Each boot: 10kV - Leakage current <10mA over

the three minute test cycle

20kV - ASTM F1117

All boots are tested with AC as standard, DC testing is available on request.

Certification

- EN ISO 20347:2012 OB I SRC HRO FO Occupational Footwear
- EN 50321-1:2018 Class 1 AC Electrically Insulating Footwear for Live Working
- ASTM F1117 (20kV)
 Dielectric Footwear
- PPE Regulation (EU) 2016/425
 Personal Protective Equipment







For use with safety boots (safety boots not included)

Sizes

	Medium	Large	Extra-Large
UK	6 - 8	9 - 11	12 - 14
EU	39 - 42	43 - 45	46 - 49
US	7 - 9	10 - 12	13 - 15

Specifications, configurations and colours are subject to change without notice.